




545 Basket Road
Webster, NY 14580

Toll Free: 800.691.0292 | Local: 585.265.1990 | Fax: 585.265.6678

www.fastenersdirect.com
sales@fastenersdirect.com

T-ANCHORS



Part Number	W Diameter Nominal	L Total Length Nominal	Drill Size	Grip Range Inches	Pull Out Strength Lbs.	Shear Strength Lbs.
	1/4	1.75	1/4	1.0	700	1500
		2.5		1.0—1.75		
		3.25		1.0—2.5		
	5/16	2.5	5/16	.875—1.5	900	2300
		3.25		1.25—2.25		
		3.75		1.875—2.75		
	3/8	3.25	3/8	1.0—2.0	1000	3000
		3.75		1.875—2.5		
		4		2.0—2.75		
		4.5		.875—3.125		

DESCRIPTION: A four-piece steel fastener consisting of (1) a partially threaded shank with a slit cut into the unthreaded end; (2) a flat, rectangular stamped toggle that swivels on a pin that attaches it to the unthreaded end of the shank; (3) a hex nut; and (4) a circular flat washer.

APPLICATIONS/ADVANTAGES: Can be used in ceilings, hollow walls, steel, concrete or wood. Requires smaller holes than toggle bolts. Applications include overhead doors, light fixtures, shelf brackets and cable television units.

MATERIAL: Carbon steel.

PROOF LOAD: T-Anchors shall meet the minimum pull out and shear values in the above table. The suggested safe working load is 1/4 the loads listed here.

PLATING: T-Anchors are typically supplied with a zinc yellow finish.